

Technical Data Sheet KASTO*hba U 13x17*

| | | |
|--|-------------|----|
| Cutting range round | 1320 | mm |
| Cutting range square | 1320 x 1320 | mm |
| Cutting range flat | 1320 x 1720 | mm |
| Smallest size to be cut approx. | Ø 500 | mm |
| Shortest length of cut-off piece | 10 | mm |
| Minimal remnant length, individual cut | 20 | mm |
| Clamping range | 500 – 1720 | mm |

Overall dimensions:

| | | |
|---|------|----|
| Length approx. | 1700 | mm |
| Width without chip conveyor approx. | 6450 | mm |
| Width with chip conveyor approx. | 7450 | mm |
| Height, saw head in lowered position, approx. | 3710 | mm |
| Height, saw head in highest position, approx. | 4250 | mm |

| | | |
|-----------------------------------|---------|---------------------|
| Material support height | 700 | mm |
| Total weight | 14100 | kg |
| Total power | 20 | kW |
| Saw motor | 11 | kW |
| Cutting speed infinitely variable | 12 – 90 | m/min with 50/60 Hz |

Cutting feed infinitely variable
 Hydraulic material feed
 Hydraulic clamping of material

Tension force:

| | | |
|--------------|-------|---|
| Machine vice | 50000 | N |
|--------------|-------|---|

| | | |
|-------------------------|------------------|----|
| Dimensions of saw blade | 13460 x 80 x 1.6 | mm |
|-------------------------|------------------|----|

| | |
|------------------------|--|
| Saw blade guide: | Carbide tipped, exchangeable |
| Saw blade tension: | Hydraulic |
| Cleaning of saw blade: | By a brush which is easy to exchange, motor-driven |
| Coolant: | Coolant supply through 3 nozzles, volume of coolant tank approx. 200 l, pump capacity 25 l/min with a pump lift of 5 m |

Energy supply:

| | |
|----------------|--|
| Mains voltage: | In accordance with EN 60204 400 V three-phase current (-10 %, +6 %) Control voltage 24 V-DC The customer will be notified of the connection value in kVA after the scope of supply has been finalized. On request other voltages for an extra charge |
|----------------|--|

| | |
|------------------|--|
| Mains frequency: | 50 Hz (-1 %, +1 %; transient -2 %, +2 %) |
|------------------|--|

| | |
|----------------|--|
| Type of mains: | TN mains according to IEC 364/VDE 0100 The power is supplied from the mains to the switching cabinets including advance fusing by the customer. The position of the switch cabinet is to be seen from the layout. |
|----------------|--|

Protective measures

| | |
|---------------------------|--|
| against indirect contact: | Over-current protector (zero balancing). The mains supply of the operator (size and characteristic of the main fuse selected as well as the total impedance of PE and |
|---------------------------|--|



outer conductor in the supply line to the machine) has to be designed in such a way that the permissible shutdown time in the event of an error is not exceeded.

The use of a differential current switch in the mains incoming supply is not permitted.

- Safety requirements:** The offered machine corresponds with the valid safety requirements according to DIN EN ISO 12100-1, DIN EN ISO 12100-2
- Painting:** Machine RAL 7035, light grey, structural painting
Blade guide arms RAL 2003, pastel-orange, structural painting
- Compressed-air supply:** Approx. 6 bar/20 l/min required