

Technical Data Sheet KASTOhbs 1 and KASTOhbs 2

Cutting range:

04/07-1

		KASTOhbs 1	KASTOhbs 2
Cutting range	90° round	210 mm	250 mm
Cutting range	90° flat (W x H)	240 x 190 mm	280 x 200 mm
Cutting range	90° flat	210 x 210 mm	250 x 250 mm
Cutting range	+ 45° round	150 mm	180 mm
Cutting range	+ 45° flat (W x H)	150 x 100 mm	170 x 200 mm
Cutting range	+ 45° flat (W x H)	130 x 210 mm	155 x 255 mm
Cutting range	+ 45° flat	145 x 145 mm	170 x 170 mm

Dimensions and weight:

Length	1190 mm	1385 mm
Width	480 mm	505 mm
Height, saw head lowered position	810 mm	960 mm
Height, saw head in highest position	1230 mm	1220 mm
Material support height	500 mm	500 mm
Material support height with rotating foundation frame (accessories)	555 mm	555 mm
Total weight	170 kg	180 kg

Power characteristics:

Total power	1,1 kW	1,3 kW
Saw motor, power	0,8 kW	1,0 kW
Average cutting speed	16/32 m/min	16/32 m/min
Stroke speed	62/125 m/min	62/125 m/min
Dimension of saw blade:	400 x 30 x 1,5 mm	450 x 40 x 2,0 mm

Electrical equipment: In accordance with DIN EN 60204
Supply voltage 400 Volt, 50 Hz.

Safety requirements: The machine is offered with reference to the valid safety requirements according to DIN EN ISO 12100-1, DIN EN ISO 12100-2

Colour: Light grey RAL 7035, Structural painting